

SPECIFICATION DATA

CHG 412 & CHG 412 PRO

12-Bay Charger



CHG 412 / CHG 412 PRO

Dimensions:	9"L x 7"W x 1.5"H (23 cm L x 17.8 cm W x 3.8 cm H)
Weight:	1.8 lbs (845 g)
Enclosure:	Black, ABS plastic with metal base
Power Supply Input:	TFP 047, 90-240 VAC input, 1.5 A max *
Power Supply:	Universal DC adapter, 5 VDC - 6A output, center positive
Charging Time:	~5 hours
Unit Capacity:	12 Units
Compatible Units:	Transceiver: DLT 400 Receiver: DLR 400 RCH
Indicators:	Charge status indicators on DLT or DLR
Case (Pro Only):	CCS 056
Approvals:	CE, FCC, WEEE, RoHS, CB
Warranty:	2-year (cables and power supply warranty for 90 days)

^{*} Eight separate CHG 412s (each powered by their own TFP 047 power supply) can be connected to a 15-amp circuit.



SPECIFICATION DATA

Architecture and Engineering Specifications

- The charger shall be a 12-bay, drop-in charger for use with the Digi-Wave™ DLT 400 and DLR 400 RCH.
- The charger shall be enclosed in black ABS plastic, 9"L x 7"W x 1.5"H (23 cm L x 17.8 cm W x 3.8 cm H).
- The charger shall weigh 1.8 lbs (845 g).
- The charger shall be powered by an external universal power supply (90-240 VAC input; 5 VDC, 6A output) via a DC barrel connector.
- Eight separate chargers, each powered by its own TFP 047 power supply, can be connected to one 15 amp circuit.
- · The charger shall have CE approval and be RoHS, WEEE, Industry Canada, FCC and CB scheme compliant.
- This charger shall be the Williams Sound model CHG 412.
- The charger housed in a carry case shall be Williams Sound model CHG 412 PRO.

Domestic Sales

Williams AV 10300 Valley View Rd Eden Prairie, MN 55344 Ph: 800-328-6190 / 952-943-2252 FAX: 952-943-2174

Email: info@williamsav.com
Web: www.williamsav.com

International Sales

International Sales Department Williams AV 10300 Valley View Rd Eden Prairie, MN 55344 USA Phone: +1 952 943 2252

Phone: +1 952 943 2252
Fax: +1 952 943 2174
Email: info@williamsav.com
Web: www.williamsav.com

