

## CS-610F/615F

(Previous models : CS-6/12)



CS-610F/615F speaker is the speaker observing the standard. It is possible to make an announcement for a long time at an emergency situation such as fire as made with the incombustible materials(V-0 grade). It is high quality speaker which can prevent from outbreak or expansion of fire caused by the speaker.

### FEATURES

- **6 inch fullrange speaker**  
· CS-610F : 10 W · CS-615F : 15 W
  - **Using high quality matching transformer (100V)**
- | Model   | Impedance |            |              |
|---------|-----------|------------|--------------|
| CS-610F | 1kΩ(10W)  | 1.7kΩ(5W)  | 3.3kΩ(3W)    |
| CS-615F | 660Ω(15W) | 800Ω(7.5W) | 1.7kΩ(3.75W) |
- **Power selection**  
Tap switch
  - **High sound pressure level and wide frequency response**  
International standard required for emergency communication speaker. Possible to play the wider frequency than 400 Hz~8 kHz
  - **Wether Resistant**  
IP 34

- **Rust prooting**  
Coating and plating for the rust prooting in order to install and operate the high humidity environment
- **a dust filter**  
Maintain the grill in the clean condition by blocking the inflow of dust with Spunbond Filter on the inside of the grill.
- **Connection / tap switch for power selection**

