



Bose ControlCenter CC-1D/CC-2D/CC-3D

digital zone controllers

Product Overview

Bose Professional ControlCenter digital zone controllers provide volume and source selection for Bose CSP, ControlSpace ESP, and ControlSpace EX sound processors. Powered using PoE, multiple processors can be used simultaneously on an Ethernet-based network. Three models are available in either black or white, feature volume/source LED indicators, and fit one-gang electrical boxes in North America, Europe, and Japan.

Key Features

Three main models: the CC-1D for simple volume control, the CC-2D for volume plus A/B source selection, and the CC-3D for volume plus A/B/C/D source selection

User-friendly interface features a single rotary encoder for volume (knob turn), source selection (knob push) and mute (knob push and hold) with an illuminated volume and source LED indication

Attractive, understated styling with two color options and regional variants to blend in seamlessly with most spaces

Networkable and PoE-powered: Ethernet-based and uses PoE for power; no special cabling or external power supplies required

Programmable: Installers can set discrete volume ranges and source options in software; multiple units can be used simultaneously in expansive projects with Bose CSP, ControlSpace ESP, and ControlSpace EX-based systems

Custom labels: Each zone controller includes a sheet of pre-printed labels, with two blanks for custom labeling

Regional variants: Each main model comes in three regional sub-models to support different sized electrical boxes. North American and Japanese models are designed for use with Decora®-style wall plate covers (not included). The 86 mm European model is supplied as a finished wall plate

Compatible with Bose CSP, ControlSpace ESP, and ControlSpace EX sound processors, and Bose PowerMatch networked amplifiers



CC-1D (NA)

CC-2D (EU)

CC-3D (JP)

Technical Specifications

| | |
|-----------------------|---|
| Connector | 1 Ethernet port (RJ-45) |
| Power | Power-over-Ethernet (PoE) switch required |
| Operating Temperature | 0° C to 40° C (32° F to 104° F) |
| Capacity | Up to 16 when using Bose CSPs or 32 units when using ControlSpace EX/ESP processors |

Product Codes

ControlSpace CC-1D

US-120V 808461-0110 (Black)
 US-120V 808461-0210 (White)
 EU-230V 808461-2110 (Black)
 EU-230V 808461-2210 (White)
 JP-100V 808461-3110 (Black)
 JP-100V 808461-3210 (White)

ControlSpace CC-2D

US-120V 808928-0110 (Black)
 US-120V 808928-0210 (White)
 EU-230V 808928-2110 (Black)
 EU-230V 808928-2210 (White)
 JP-100V 808928-3110 (Black)
 JP-100V 808928-3210 (White)


ControlSpace CC-3D

US-120V 808930-0110 (Black)
 US-120V 808930-0210 (White)
 EU-230V 808930-2110 (Black)
 EU-230V 808930-2210 (White)
 JP-100V 808930-3110 (Black)
 JP-100V 808930-3210 (White)


Bose ControlCenter CC-1D/CC-2D/CC-3D

digital controllers


CC-1D, EU, JP, US




Front View




Right View
DIMENSIONS APPLY TO BOTH SID




Front View



Right View
DIMENSIONS APPLY TO BOTH SID




Front View




Right View
DIMENSIONS APPLY TO BOTH SID


CC-2D, EU, JP, US




Front View




Right View
DIMENSIONS APPLY TO BOTH SID




Front View



Right View
DIMENSIONS APPLY TO BOTH SID




FRONT VIEW




RIGHT VIEW
DIMENSIONS APPLY TO BOTH SID


CC-3D, EU, JP, US




Front View




Right View
DIMENSIONS APPLY TO BOTH SID




FRONT VIEW



RIGHT VIEW
DIMENSIONS APPLY TO BOTH SID



FRONT VIEW



RIGHT VIEW
DIMENSIONS APPLY TO BOTH SID

For additional specifications and application information, please visit PRO.BOSE.COM. Specifications subject to change without notice. 01/2019