

XWO-BKT1

WHAT THIS PRODUCT DOES:

Use two or more Wireless Outdoor Bridging APs to provide connectivity to remote locations such as an outbuilding or guest house; or to connect IP cameras and other devices. The XWO-BKTI Kit combines leading-edge dual-band 802. Tlac Wi-Fit technology with high output power. The units come pre-configured and paired for simple setup. The reliable and rugged IP-65 rated design offers flexible pole or wall mounting options—making it a great choice for delivering superior outdoor wireless bridging and coverage.

Residential Applications:

- Bridge to Guest House, Boat Dock or Garage
- ► Connect Gates and Cameras
- ► Outdoor/Pool Coverage

Commercial Applications:

- Bridge to Warehouse, Shop or other Buildings
- ► Outdoor Connectivity
- ► Cameras and Security

FEATURES:

- ► Concurrent Dual-Band 2.4 and 5 GHz
- High Output Power for Maximum Coverage
- ► Data Transfers up to 1200Mbps
- ► 802.11ac (up to 1200Mbps)
- Support for Point-to-Point and Point-to-Multipoint Wireless Bridging
- ▶ Up to 4 SSIDs per Band (8 Total)
- ▶ 802.3at PoE Powered
- ► Weather Resistant Enclosure (IP-65)
- ► Pole or Wall Mount
- ► Three Year Limited Warranty

This Kit includes everything needed for outdoor Wi-Fi bridging and coverage, including two access points, PoE injectors and flexible mounting hardware.

High Power AC1200 Dual-Band Outdoor Bridge Kit





XWO-BKT1 TECHNICAL SPECIFICATIONS*

Hardware Features

Standards Compliance	802.11b/g/n/ac
Interface	One 10/100/1000M Port
Antenna	Two Internal 2.4GHz(7dbi). Two Internal 5GHz(12dbi)
Button	Reset button
Power	802.3at PoE
Power Consumption	17W on average (Depending on the Wireless activity)
Max Power Consumption	16.8W
Environmental Temperatures	-20-50c
Dimensions WxHxD in. (mm)	9"x9"x1.9" (229 x229 x149)
Weights lbs (kg)	2.9 (1.31)

Wireless and Other Features	
Frequency	2.4GHz, 5GHz
Wireless Speed	▶ 2.4GHz: 300Mbps;▶ 5GHz: 866Mbps.
Output Power	30dBm
Wireless Security	WPA-PSK, WPA2-PSK, WPA/WPA2/AES
Operating Modes	Wireless AP
Performance**	 ► 5 GHz - up to 500 Mbps at 1/4 Mile ► 5 GHz - up to 435 Mbps at 1/2 Mile ► 2.4 GHz - up to 90 Mbps at 1/2 Mile
Other Functions and Features	 Remote Web Management System Logging Backup & Restore Configurations VLAN/Guest Network Support QoS Support Up to 4 SSIDs Firmware Upgradeable via Browser

^{*}All Technical Specifications Represent One Wireless Outdoor Bridging AP

Certifications FCC, RoHS, IC, RCM

All references to speed are for comparison purposes only. Product specifications, size and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.

Warranty

► Three year limited warranty

Minimum Requirements

- Web browser
- ► Ethernet cable
- Internet connection to view documentation online

Package Contents

- ► XWO-BAP1 Outdoor Bridging AP (2)
- PoE Injector (2)
- ► Mounting Kit (2)
- ► Water Resistant Cable Gland (2)
- ► Ethernet Cable (2)
- Quick Install Guide

^{**}Line of sight and without obstructions. Speed, performance, and connectivity may be affected by interference from the local environment.