

SPK-080




Fits TVs
42"-86"



Bluetooth®



All Weather Rated



Xtreme™ Outdoor Soundbar

Immerse yourself in outdoor entertainment at its finest with the amplified, outdoor soundbar by Peerless-AV®. Whether there's rain, snow, ice or heat, the Xtreme™ Outdoor Soundbar can withstand even the most extreme outdoor environments with its IP65 rating. For ease of use and installation, this soundbar features a universal mounting option and both analog and optical connections, making it possible to integrate with any display or TV. Plus, set-up is simple with a direct-wired connection. With additional features such as Bluetooth® Connectivity, high quality drivers that provide full range audio (50Hz – 20Hz), and a built-in Class D amplifier that outputs 200 watts of total system power, your outdoor entertainment gets a complete audio upgrade.

The perfect all-season solution for outdoor entertainment, the Xtreme™ Outdoor Soundbar is easy to use and offers unprecedented audio quality and power.

Additional Features

- ✓ Built-in Class D amplifier outputs 200W total system power
- ✓ IP65 rated aluminum enclosure features rubber gaskets at every seam that completely seal, isolate and protect the soundbar's electronics from the outside environment
- ✓ High quality drivers provide great sounding full range audio (50Hz - 20kHz)
- ✓ Control the power level, tone, and input selection with the 12 button IR remote control*
- ✓ Easily mounts to the Peerless-AV® Xtreme™ Outdoor Displays and UltraView™ Outdoor TVs with the included outdoor rated mounting hardware
- ✓ Digital optical audio input allows for uncompressed digital audio from source

* Control codes available in the the Peerless-AV weatherproof remote control, sold with the Peerless-AV Xtreme™ displays and UltraView™ TVs

IP65 RATED

Withstands the harshest outdoor weather conditions year round

COMPATIBILITY

Provides a digital optical audio input and standard analog input, allowing for use with all leading outdoor TVs



DECORATIVE END CAPS

Aesthetically enhance any mounting scenario



BUILT-IN BLUETOOTH® MODULE

Wirelessly stream audio from Bluetooth® enabled devices



Compatible with all leading Outdoor TVs



SPK-080 Xtreme™ Outdoor Soundbar

Product Specifications

TV SIZE RANGE	42" (107cm) and Above
BUILT-IN CLASS D AMPLIFIER	Total System Power: 200 watts
SPL	105dB
CROSSOVER	Digital Signal Processing (DSP)
DRIVERS	(2) 3" (76mm) Aluminum Drivers
TWEETERS	(2) 1.5" (38mm) Titanium Domes

AUDIO INPUTS	(1) Digital Optical Audio Input, (1) Analog 3.5mm Connector, (1) Bluetooth® 4.0 Input
ENVIRONMENTAL PROTECTION RATING	IP65
FREQUENCY RESPONSE	50Hz - 20kHz
OPERATING TEMPERATURE RANGE	-40° - 120°F (-40° - 49°C)
VESA®	400mm Wide Pattern
PRODUCT DIMENSIONS	38.13" x 3.91" x 4.32" (969 x 99 x 110mm)
PRODUCT WEIGHT	9.7lb (4.4kg)

Package Specifications

	PACKAGE SIZE (W x H x D)	PACKAGE SHIP WEIGHT	PACKAGE UPC CODE	PACKAGE CONTENTS	UNITS IN PACKAGE
SPK-080	39.50" x 7.25" x 9.50" (1003 x 184 x 241mm)	18.02lb (8.17kg)	735029318088	Soundbar, (2) End Caps, Power Cable, 3.5 Analog Input Cable, Mounting Hardware, 12 Button IR Remote, User Manual, , Digital Optical Audio Cable	1

All dimensions = inch (mm)



TOP VIEW



FRONT VIEW



SIDE VIEW

Architect Specifications

The Xtreme™ Outdoor Soundbar shall be a Peerless-AV model SPK-080 and shall be located where indicated on the plans. Assembly and installation shall be done according to instructions provided by the manufacturer.

Visit peerless-av.com to see the complete line of AV solutions from Peerless-AV, including outdoor displays, wireless, kiosks, digital audio, display mounts, projector mounts, carts/stands, and a full assortment of accessories.

Peerless-AV
2300 White Oak Circle
Aurora, IL 60502 USA
(800) 865-2112
(630) 375-5100
Fax: (800) 359-6500

Peerless-AV Europe
Unit 3 Watford Interchange
Colonial Way, Watford
Herts, WD24 4WP
United Kingdom
+44 (0) 1923 200100
Fax: +44 (0) 1923 200101

Peerless-AV de México
Ave de las Industrias 413
Parque Industrial Escobedo
Escobedo, N.L.,
Mexico 66050
+52 (81) 8384-8300
Fax: +52 (81) 8384-8360

