

Whether it's on-stage or in the studio, Furman Pro Plugs give you the protection you need. With surge protection, noise filtration, and diagnostic lighting, you can trust Furman Pro Plugs for reliable, clean, and protected power. Our products have saved billions of dollars worth of equipment from power problems, and our innovative technologies maximize system performance.



Six outlet power conditioners with standard surge protection, EMI/RFI filtration, heavy duty steel construction, and 15 ft. power cords.

The SS-6B-Pro includes the Furman EVS (Extreme Voltage Shutdown) technology that will disconnect the power conditioner from the AC mains to protect your connected equipment as well as itself. The high shutdown is set at 140 Vac +/- 5% while the low shutdown is set at 95 Vac +/- 5%.

POWER CONDITIONERS

SS-6



15 A	OK *	6
15A Rating	Diagnostic Lights	6 Outlets
Standard Level Surge Protection	Standard Level RFI/EMI Filtration	

SS-6B



15 A	OK *	6		
15A Rating	Diagnostic Lights	6 Outlets	Standard Level Surge Protection	Standard Level RFI/EMI Filtration

SS-6B-Pro



15 A	OK *	6			EVS EXTREME VOLTAGE SHUTDOWN
15A Rating	Diagnostic Lights	6 Outlets	Standard Level Surge Protection	Standard Level RFI/EMI Filtration	EVS Voltage Protection

POWER DISTRIBUTION UNITS



15 A	5
15A Rating	5 Outlets

PlugLOCK

Lock your plugs and transformers in place, ensuring you never get disconnected from your power source



ACX-25

Discreet, 25 ft. power cord provides ultimate durability and longevity

15 A	3
15A Rating	3 Outlets



POWER CONDITIONERS

SS-6

SS-6B

SS-6B-Pro

AC Protection Technology	Standard spike and surge protection UL VPR:400V, UL Nominal	Standard spike and surge protection UL VPR:400V, UL Nominal	Standard spike and surge protection UL VPR:400V, UL Nominal
Signal Pulse Energy Dissipation	540 Joules	540 Joules	540 Joules
Filtration Technology	Standard level RFI/EMI filtration Filter: -20dB Min, 100kHz – 1MHz	Standard level RFI/EMI filtration Filter: -20dB Min, 100kHz – 1MHz	Standard level RFI/EMI filtration Filter: -20dB Min, 100kHz – 1MHz
Under-Voltage Shutoff	—	—	95VAC +/- 5%
Over-Voltage Shutoff	—	—	140VAC +/- 5%
Dimensions	2.5"W x 1.5"D x 14.5"H	3.5"W x 1.5"D x 9.5"H	3.5"W x 1.5"D x 9.5"H
Weight	2.52lbs	2.64lbs	2.64lbs
AC Power Cord	15ft. captive cord (14AWG)	15ft. captive cord (14AWG)	15ft. captive cord (14AWG)
Outlets	6	6	6
Line Voltage	120V	120V	120V
Current Rating	15 amps	15 amps	15 amps
Safety Listing	cULus	cULus	cULus
Warranty	1 year	1 year	1 year



POWER DISTRIBUTION UNITS

PlugLOCK

ACX-25

Dimensions	2.3"W x 2.5"D x 12.6"H	—
Weight	2.125lbs	3lbs
AC Power Cord	5ft. captive cord (14AWG)	25ft. (14AWG)
Outlets	5	3
Line Voltage	120V	120V
Current Rating	15 amps	15 amps
Safety Listing	cCSAus	cULus
Warranty	1 year	1 year



#1 in Power Protection for Over 40 Years

Product Video



To find your local Furman Dealer or Regional Sales Representative, please visit:

www.FurmanPower.com