LUXUL

Simply Connected[™]

XAP-1510

WHAT THIS PRODUCT DOES:

The XAP-1510 combines leadingedge 802.11ac technology with high output power to deliver outstanding dual-band Wi-Fi performance. The sleek design allows for unobtrusive mounting on a ceiling, wall or other flat surface—making it a great choice for maximizing coverage in both Residential and Commercial environments. It is compatible with the XWC-1000 Wireless Controller and can be used standalone or as part of a multi-AP deployment. Installation is simple, requiring only a single Ethernet cable that delivers both power and data through the integrated PoE+ port.

- High Performance 802.11ac
 Wi-Fi (up to 1900Mbps)
- Concurrent Dual-Band with Beamforming
- Compatible with XWC-1000 Wireless Controller
- Great for Streaming Media and Other Demanding Applications
- Secure Guest Networking
- Simple and Discreet Installation

FEATURES:

- High Output Power for Maximum Coverage
- Beamforming for Optimal Wi-Fi Performance
- Data Transfers of up to 1900Mbps
- Concurrent Dual-Band
- Compatible with the Luxul XWC-1000 Wireless Controller
- VLAN Support for Creating a Secure Guest Network
- Up to 4 SSIDs per Band for a total of 8 SSIDs
- Single Cable Installation with PoE (Injector included)
- Installs on Ceiling or Wall; Or Use as a Desktop AP
- Three Year Limited Warranty

High Power AC1900 Dual-Band Wireless AP



XAP-1510 TECHNICAL SPECIFICATIONS

Internet Connection to View

Documentation Online

| Hardware Features | |
|---|---|
| Standards Compliance | IEEE, 802.11b/g/n, 802.11a/n/ac, 802.3at |
| Interface | Two 10/100/1000M Ports |
| Antenna | Three Dual-Band Antennas |
| Button | Reset button |
| Power | PoE (Injector Included) |
| Power Consumption | 10W Idle 25.3W Peak |
| Environment Tempatures | 0-50C° |
| Dimensions WxHxD in. (mm) | 7.25"x7.25"x2" (184.15 x184.15 x50.8) |
| Weight lbs (kg) | 1.5 (.68) |
| LEDs | Power, 2.4GHz, 5GHz (Can be turned Off/On Via User Interface) |
| Wireless and Other Features | |
| Frequency | Concurrent 2.4GHz and 5GHz with Beamforming |
| Wireless Speed | 2.4GHz: 600Mbps; 5GHz: 1.3Gbps |
| Wireless Security | WPA-PSK, WPA2-PSK, WPA/WPA2 |
| Operating Modes | Wireless AP |
| Other Functions and Features | Remote Web Management System Logging Backup & Restore Configurations VLAN/Guest Network Support Up to 4 SSIDs per Band for a total of 8 SSIDs Firmware Upgradeable via UI XWC-1000 Wireless Controller Compatible |
| Certifications | CE, FCC, RoHS |
| Warranty: Three Year Limited Warranty Minimum Requirements Web Browser Ethernet Cable | Package Contents One: High Power AC1900 Dual-Band AP One: Mounting Bracket and Hardware One: PoE Injector and Power Adapter One: Quick Install Guide |

All references to speed are for comparison purposes only. Product specifications, size and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.

a: 14203 Minuteman Drive, Suite 201, Draper, UT 84020-1685 | p: 801-822-5450 | luxul.com © Copyright 2015 Luxul All rights reserved. The name Luxul, the Luxul logo, the Luxul logo, the All simply Connected are all trademarks and o requirement reference of the Will Wirelese. The All other trademarks are demitted to reference to the bulker is a structure of the All other trademarks and one of the Million of the All other trademarks and one of the Million of the All other trademarks are also as the All other trademarks are also as the All other trademarks are also as the Million of the All other trademarks are also as the All other